



Type KSV

Stem extension (silding T-wrench)



Type KSV



Type KSV-VR

Locking Device at the top



Type KSV-P

with plunger arrestor

- applicable for all AZ valves
- standard extension 100mm or 150mm

Design characteristics


- solid construction made of stainless steel 1.4308, ASTM A351 CF8
- simple mounting
- for extended operation
- for thick-walled insulation
- push-through in tight spaces conditions
- two-hand operation

Options

- special material
- other heights
- locking device
- plunger arrestor

Type KSV

Technical information



for multiport valves:
position indicator welded on KSV, stainless steel

DN	B [mm]	SW [mm]	H (KSV) [mm]	H (KSV-VR) [mm]	H1 [mm]	øN [mm]	R [mm]
15	15	11	100/150*	100	103	10	225
15E	15	11	100/150*	100	103	10	225
20	15	11	100/150*	100	103	10	225
20E	15	11	100/150*	100	97	10	225
25	15	11	100/150*	100	97	10	225
25E	20	14	100/150*	100	109	15	360
32	20	14	100/150*	100	97	15	360
32E	25	19	100/150*	100	109	20	465
40	20	14	100/150*	100	97	15	360
40E	25	19	100/150*	100	109	20	465
50	25	19	100/150*	100	109	20	465
65	25	22	100/150*	100	106	25	665
80	25	22	100/150*	100	106	25	665
100	25	22	100/150*	100	106	25	665
100S	25	22	100/150*	-	-	25	665

*) Standard heights 100 or 150 mm, others on request